

PRODUCT DATA SHEET



1. SHOTGUN AMMUNITION – PRACTICE & TRAINING 12G Cartridge T-LESS Blank

Primetake Part - PT3581
Catalogue No. 01.03.3581
Version 3

Product and Packing Details

| | |
|------------------------|---------------------------------------------|
| WEIGHT | 11.40g approx |
| CHAMBER LENGTH | 76mm |
| NET EXPLOSIVE QUANTITY | 0.002g approx |
| SHELF LIFE | 5 years under controlled storage conditions |
| RANGE | This round has a 2 metre safety zone |
| PACKAGING | FIBREBOARD |
| DIMS mm | 340x240x140 |
| QTY PER OUTER PACK | 250 |
| GROSS WEIGHT NOMINAL | 3.47kg |
| MAXIMUM NEQ | 0.0005kg |
| PROPER SHIPPING NAME | Cartridges for weapons, blank |
| UN SERIAL NUMBER | 0014 |
| HAZARD CLASS | 1.4S |



Methods of Use

The 12G T-Less Blank is the alternative to the Tea Blank where the requirement to simulate entry tactics does not need a loud report, smoke and flame. Instead it will produce the nominal sound of the primer.

Description

The round consists of only a primer and a white top card. The 12G T-Less Blank is supplied in a green plastic cartridge case.

Performance/Safety

Use in Magnum proofed unchoked shotguns only. Not to be fired through 12 Gauge pistols or other shotguns, including semi-automatic.

Range Safety Template available on request.

Articles should remain within the original sealed package and be stored within a temperature controlled environment of +5°C to +30°C; relative humidity should not exceed 70%. Storage outside of these conditions will not be warranted and may reduce the shelf life and lead to the articles not functioning as intended.

At Primetake we constantly review our products—all specifications are a guide and may vary so please check that the latest specification meets your requirements

Reepham Road, Fiskerton, Lincoln, LN3 4EZ, United Kingdom Phone: +44 (0)1522 752323 Fax: +44 (0)1522 752484
Email: sales@primetake.com Web: www.primetake.com