

## PRODUCT DATA SHEET

PT1526A

VERSION 8



### OVERVIEW

## 12 Gauge - Distraction & Crowd Control

Code: PT1526A

Cal: 12 Gauge

**Cartridge, Shotgun, 12G, Irritant, Short Range, HP (Non Waterproof)**

### Description

The Short Range IMP (Irritant Multi Purpose) round is designed for use in operations where CS deployment is required. It can be fired at close range, with a recommended stand-off distance of 25mm from the target and produces an immediate, large volume cloud of CS particles up to 10 metres behind a barricade.

The round can be deployed against doors and windows with the ability to disrupt locks and hinges. It can also be deployed against soft skinned vehicles.

The round incorporates a loose filled payload mixture of micronized CS and refined Bismuth powder, which reduces the risk of ricochet and over penetration.

### SPECIFICATION

**Payload:** Micronised CS powder / Refined Bismuth powder mix  
**Case Material:** Translucent Plastic / Brass Ferrule  
**Operational Temperatures:** -21°C to +63°C  
**Safety Temperatures:** -45°C to +71°C  
**Penetration:** 30-60 minute fire door  
**Recommended Stand-Off:** 25mm  
**Mean Chamber Pressure:** 400 - 600 bar  
**Propellant Type:** Double Based Nitrocellulose  
**Primer Type:** Shotgun Primer  
**Weapon Compatibility:** 3" chamber magnum proofed shotgun (true cylinder - unchoked)

### TRANSPORT & PACKAGING DETAILS

<b>Packaging:</b> M2A1	<b>Packaging:</b> Fibreboard Box
<b>Dimensions mm:</b> 306x156x192	<b>Dimensions mm:</b> 340x240x140
<b>Qty per Outer Pack:</b> 120	<b>Quantity Per Outer Pack:</b> 200
<b>Gross Weight:</b> 9.68kg	<b>Gross Weight:</b> 11.60kg
<b>Maximum NEQ:</b> 0.205kg	<b>Maximum NEQ:</b> 0.341kg

**Proper Shipping Name:** Ammunition, tear producing

**UN Serial Number:** 0301

**Hazard Class:** 1.4G (6.1 & 8)

**Shelf Life:** 3 years under controlled conditions

**Storage requirements:** To remain within original packaging, stored between +5°C to +30°C with a relative humidity not exceeding 70%.

Find out more

[sales@primetake.com](mailto:sales@primetake.com)

We are constantly reviewing our products. All specifications are to be used as a guide and may vary so please check that the specification meets your requirements.