

## PRODUCT DATA SHEET

PT1029

VERSION 6



### OVERVIEW

## 12 Gauge - Practice & Training

Code: PT1029

Cal: 12 Gauge

**12G Saluting Blank - Helston**

### SPECIFICATION

Case Material: Black Plastic / Brass Ferrule

Cartridge Length: 25mm

Operational Temperatures: -21°C to +63°C

Safety Temperatures: -45°C to +71°C

Range: NIL

Propellant Type: Black Powder

Primer Type: Shotshell Primer

Weapon Compatibility: 12 gauge pump-action shotguns  
and compatible impact grenades only

### TRANSPORT & PACKAGING DETAILS

Packaging: Fibreboard Box

Dimensions mm: 340x240x140

Quantity Per Outer Pack: 500

Gross Weight: 4.99kg

Maximum NEQ: 1.14kg

Proper Shipping Name: Cartridges for weapons, blank

UN Serial Number: 0014

Hazard Class: 1.4S

Shelf Life: 5 years under controlled conditions

Storage requirements: To remain within original packaging,  
stored between +5°C to +30°C with a relative humidity not  
exceeding 70%.

Storage outside of these conditions will not be warranted  
and may reduce the shelf life and lead to the articles not  
functioning as intended.

### Description

The Helston Blank round can be used as a general training round for a shotgun or within some impact distraction grenades such as the Helston Grenade. The Helston Blank Cartridge has been specifically designed as a low-energy training cartridge to simulate firing but without producing damage.

Range safety template available on request.

Find out more

**sales@primetake.com**

We are constantly reviewing our products. All specifications are to be used as a guide and may vary so please check that the specification meets your requirements.