

PRODUCT DATA SHEET

PT1034A

VERSION 6



OVERVIEW

12 Gauge - Practice & Training

Code: PT1034A

Cal: 12 Gauge

Projectile Weight: 30 gram

Cartridge, Shotgun, 12G, Long Range, Irritant, Practice (Non Waterproof)

Description

The Long Range IMP (Irritant Multi Purpose) Practice round is designed for use during training operations to simulate deployment of 'live' CS. It has an effective range up to and including 35 metres, which produces an immediate, large volume cloud of chalk particles up to 10 metres behind a barricade.

The round incorporates a frangible projectile filled with chalk and stainless steel powder, which reduces the risk of ricochet and over penetration.

SPECIFICATION

Payload: Calcium Carbonate / Stainless Steel powder mix

Case Material: Blue Plastic / Brass Ferrule

Operational Temperatures: -21°C to +63°C

Safety Temperatures: -45°C to +71°C

Mean Velocity: 350 - 400m/s at 2 metres

Accuracy: 1m x 1m Target at 35 metres

Penetration: 30-60 minute fire doors/commercial glass

Mean Chamber Pressure: 400 - 600 bar

Range: Up to 35 metres

Propellant Type: Double Based Nitrocellulose

Primer Type: Shotshell Primer

Weapon Compatibility: 3" chamber magnum proofed shotgun (true cylinder - unchoked)

TRANSPORT & PACKAGING DETAILS

Packaging: M2A1

Packaging: Fibreboard Box

Dimensions mm: 306x156x192

Dimensions mm: 340x240x140

Qty per Outer Pack: 120

Quantity Per Outer Pack: 200

Gross Weight: 8.61kg

Gross Weight: 9.82kg

Maximum NEQ: 0.196kg

Maximum NEQ: 0.272kg

Proper Shipping Name:

Proper Shipping Name:

Cartridges, small arms

Cartridges for weapons, inert projectile

UN Serial Number: 0012

Hazard Class: 1.4S

Shelf Life: 5 years under controlled conditions

Storage requirements: To remain within original packaging, stored between +5°C to +30°C with a relative humidity not exceeding 70%.

Find out more

sales@primetake.com

We are constantly reviewing our products. All specifications are to be used as a guide and may vary so please check that the specification meets your requirements.