



## PRODUCT DATA SHEET

PT1571F

VERSION 8



### OVERVIEW

## Brass Ammunition

Code: PT1571F

Projectile Weight: 300 grains

**8.6 x 70mm (0.338") 300gn OTM**

### Description

The Primetake Omega Sniper Ammunition has been designed as a highly accurate long range round, intended for use in high quality rifle/scope combinations of bolt action and semi-automatic rifles. For use where accuracy is a primary requirement.

Primetake's Omega Sniper range is manufactured with the highest quality components to the tightest tolerances achievable. Each production lot undergoes meticulous load development to guarantee optimised accuracy, velocity and minimal velocity spread thus resulting in a range of sniper ammunition that enjoys unrivaled hit probability at extreme ranges. Performance is dependent on the quality and specification of the selected firearm and atmospheric conditions.

This cartridge has a 300gn Open Tip Match projectile with a boat tail feature and is non-expanding.

Range Safety Template available on request.

### SPECIFICATION

Projectile Material: Copper, Lead

Case Material: CuZn Alloy

Operational Temperatures: -54°C to +52°C

Safety Temperatures: -54°C to +63°C

Muzzle Velocity:  $\geq 808$  m/s

Accuracy:  $\leq 1$  M.O.A

Ballistic Coefficient: G1 - 0.742 G7 - 0.380

Mean Chamber Pressure:  $\leq 4200$  Bar

Range:  $\geq 1600$ m

Optimal Barrel Twist Rate: 1:10

Propellant Type: Double Based (single base available)

Primer Type: Large Rifle Magnum Boxer

Weapon Compatibility: CIP / SAAMI

### TRANSPORT & PACKAGING DETAILS

Packaging: M2A1

Dimensions mm: 306x156x192

Qty per Outer Pack: 160

Gross Weight: 12.57kg

Maximum NEQ: 1.204kg

Proper Shipping Name: Cartridges, small arms

UN Serial Number: 0012

Hazard Class: 1.4S

Shelf Life: 10 years under controlled conditions

Storage requirements: To remain within original packaging, stored between +5°C to +30°C with a relative humidity not exceeding 70%.

Storage outside of these conditions will not be warranted and may reduce the shelf life and lead to the articles not functioning as intended.

Find out more

[sales@primetake.com](mailto:sales@primetake.com)

We are constantly reviewing our products. All specifications are to be used as a guide and may vary so please check that the specification meets your requirements.