

PRODUCT DATA SHEET

PT3504A

VERSION 7



OVERVIEW

Brass Ammunition

Code: PT3504A

Projectile Weight: 168 grains

7.62 x 51mm (0.308") 168gn OTM

Description

The Primetake Omega Sniper Ammunition has been designed as a highly accurate long range round, intended for use in high quality rifle/scope combinations of bolt action and semi-automatic rifles. For use where accuracy is a primary requirement.

Primetake's Omega Sniper range is manufactured with the highest quality components to the tightest tolerances achievable. Each production lot undergoes meticulous load development to guarantee optimised accuracy, velocity and minimal velocity spread thus resulting in a range of sniper ammunition that enjoys unrivaled hit probability at extreme ranges. Performance is dependent on the quality and specification of the selected firearm and atmospheric conditions.

This cartridge has a 168gn Open Tip Match projectile with a boat tail feature and is non-expanding. Range Safety Template available on request.

SPECIFICATION

Projectile Material: Copper, Lead Antimony

Case Material: CuZn Alloy

Operational Temperatures: -54°C to +63°C

Safety Temperatures: -54°C to +71°C

Muzzle Velocity: \geq 840 m/s

Accuracy: \leq 1 M.O.A

Ballistic Coefficient: G1 - 0.426 G7 - 0.218

Mean Chamber Pressure: \leq 4150 Bar

Range: 1000m

Optimal Barrel Twist Rate: 1:10 to 1:12

Propellant Type: Double Based (single base available)

Primer Type: Large Rifle Berdan (Boxer available)

Weapon Compatibility: CIP / SAAMI

TRANSPORT & PACKAGING DETAILS

Packaging: M2A1

Dimensions mm: 306x156x192

Qty per Outer Pack: 400

Gross Weight: 13.10kg

Maximum NEQ: 1.18kg

Proper Shipping Name: Cartridges, small arms

UN Serial Number: 0012

Hazard Class: 1.4S

Shelf Life: 10 years under controlled conditions

Storage requirements: To remain within original packaging, stored between +5°C to +30°C with a relative humidity not exceeding 70%.

Storage outside of these conditions will not be warranted and may reduce the shelf life and lead to the articles not functioning as intended.

Find out more

sales@primetake.com

We are constantly reviewing our products. All specifications are to be used as a guide and may vary so please check that the specification meets your requirements.