



PRODUCT DATA SHEET

PT1522B

VERSION 7



OVERVIEW

Ceremonial/Saluting

Code: PT1522B

Powder Charge: 454g

Cartridge, 25Pdr Blank, 454g

O

Charge (Modular)

SPECIFICATION

Case Material: Anodised Aluminium (brass coloured)

Overall Length: 278mm

Operational Temperatures: -21°C to +49°C

Propellant Type: Black Powder

Primer Type: 0.50" cal Percussion Primer Weapon Compatibility: 25 Pounder Field Gun

TRANSPORT & PACKAGING DETAILS

Packaging: Plywood Box

Dimensions: 500 x 280 x 320

Qty per Outer pack: 8

Gross Weight: 22.56kg approx.

Maximum NEQ: 3.633kg

Proper Shipping Name: Cartridges for weapons, blank

UN Serial Number: 0326

Hazard Class: 1.1C

Shelf Life: 5 years under controlled conditions Storage requirements: Articles should remain within the original sealed packaging; within a temperature range of +5°C to +30°C where the relative humidity does not exceed 70%.

Storage outside of these conditions will not be warranted and may reduce the shelf life and lead to the articles not functioning as intended.

Description

The 25Pdr Blank is designed to be used for saluting and ceremonial purposes. The cartridge emits smoke and a loud report upon firing; without leaving any burning debris on the ground.

The cartridge design consists of an anodised aluminium, brass coloured two-piece case which houses a percussion primer in the base, used to ignite the black powder charge. The modular design contains 3 x 113.5g charge bags to allow the user to select the desired charge.

The Cartridge is designed to be fired through a 25 Pounder Field Gun.

Range Safety Template available on request. Primetake's internal testing/ proofing methodology and weapon specification available on request.