



PRODUCT DATA SHEET

PT4515

VERSION 4



OVERVIEW

Specialist Small Arms

Code: PT4515

Projectile Weight: 90 grains

9 x 19mm Counter Terror

Description

Primetake's 9 x 19mm COUNTER TERROR cartridge has been specifically designed for the Military & Law Enforcement professional, offering unrivalled expansion and wound cavity in soft tissue. The 9mm CT cartridge is ideal for CQB (Close Quarter Battle) situations by specialist and elite units where minimising collateral damage is essential.

The projectile features a ballistic tip which prevents the cavity from becoming blocked and aids rapid and controlled expansion.

The projectile has been specifically designed for reducing collateral damage but at the same time retaining a high level of stopping power and controlled terminal ballistic effects. The projectile materials are completely free from lead material and are REACH compliant.

CONTINUED

SPECIFICATION

Projectile Material: Copper

Case Material: CuZn Alloy

Operational Temperatures: -30°C to +54°C

Safety Temperatures: -30°C to +71°C

Muzzle Velocity: 400 m/s approx.

Penetration: ≤ 12" 10% Gelatin

Mean Chamber Pressure: ≤ 2350 Bar

Propellant Type: Double Based

Primer Type: Pistol Primer

Weapon Compatibility: Pistol, PDW, SMG

TRANSPORT & PACKAGING DETAILS

Packaging: M2A1

Dimensions mm: 306x156x192

Qty per Outer Pack: 1000

Gross Weight: 13.95kg

Maximum NEQ: 0.608kg

Proper Shipping Name: Cartridges, small arms

UN Serial Number: 0012

Hazard Class: 1.4S

Shelf Life: 10 years under controlled conditions

Find out more

sales@primetake.com

We are constantly reviewing our products. All specifications are to be used as a guide and may vary so please check that the specification meets your requirements.



Performance/Safety

The 9mm Counter Terror (CT) round has been specifically designed to function safely and effectively to C.I.P. safe working pressures at temperatures ranging from -20°C to +52°C.

The 9mm Counter Terror (CT) round cycles and functions through both the 9mm Glock 17 pistol and the 9mm MP5 SMG at all of these operating temperatures, with exceptional close quarter combat accuracy at distances up to and including 15 metres for the pistol and 50 metres for the MP5. The 9mm Counter Terror (CT) round also has a bullet extraction force compliant to MOPI specifications, enabling it to be constantly re-cycled through semi- automatic weapons. These results were obtained under test conditions and Primetake recommends customers make their own assessments based on their own operational requirements.

Range Safety Template available on request.

Articles should remain within the original sealed package and be stored within a temperature controlled environment of +5°C to +30°C; relative humidity should not exceed 70%. Storage outside of these conditions will not be warranted and may reduce the shelf life and lead to the articles not functioning as intended.