

PRODUCT DATA SHEET

PT1506

VERSION 5



OVERVIEW

Demolition Accessories

Code: PT1506

Igniter Safety Fuze Electric

SPECIFICATION

Weight: 4.50g approx

Net Explosive Quantity: 0.16g approx

Description

The primary function of the Primetake ISFE is to ignite a safety fuse via electrical means.

The Igniter Safety Fuze Electric (ISFE) is an igniter which consists of an electric fuse head crimped into a copper tube with a vent hole on the side. The tube has an integral stop to ensure correct fitting of safety fuse and has immediate functioning upon initiation with a chosen activating device.

TRANSPORT & PACKAGING DETAILS

Packaging: M2A1

Dimensions mm: 306x156x192

Quantity Per Pack: 320

Gross Weight: 4.57kg

Maximum NEQ: 0.0512kg

Proper Shipping Name: Fuzes, igniting

UN Serial Number: 0368

Hazard Class: 1.4S

Shelf Life: 3 years under controlled storage conditions

Storage requirements: To remain within original packaging, stored between +5°C to +30°C with a relative humidity not exceeding 70%.

Storage outside of these conditions will not be warranted and may reduce the shelf life and lead to the articles not functioning as intended.

Find out more

sales@primetake.com

We are constantly reviewing our products. All specifications are to be used as a guide and may vary so please check that the specification meets your requirements.