

in





PRODUCT DATA SHEET

PT1574

VERSION 4



OVERVIEW

Demolition Accessories

Code: PT1574

Igniter Safety Fuze Percussion

SPECIFICATION

Weight: 27.60g approx Nominal Length: 100mm

Net Explosive Quantity: 0.00052g approx

Description

The primary function of the Primetake
ISFP is to ignite a safety fuse via an enclosed striker
upon release of a safety clip.

The Igniter Safety Fuze Percussion (ISFP) is an igniter which consists of a CCI-500 percussion primer within an injection moulded housing. A safety ring is attached to a safety "R" clip which primes the cocked striker. The body comes in deep bronze green and black.

Performance/Safety

Immediate functioning after removal of the safety ring initiating cocked striker.

TRANSPORT & PACKAGING DETAILS

Packaging: M2A1

Dimensions mm: 306x156x192

Quantity Per Pack: 60 Gross Weight: 4.65kg Maximum NEQ: 0.0015kg

Proper Shipping Name: Primers, cap type

UN Serial Number: 0044

Hazard Class: 1,4S

Shelf Life: 3 years under controlled storage conditions Storage requirements: To remain within original

packaging, stored between +5°C to +30°C with a

relative humidity not exceeding 70%.

Storage outside of these conditions will not be warranted and may reduce the shelf life and lead to the articles not functioning as intended.