y in D





OVERVIEW **12 Gauge - Irritant** Code: PT1038A Cal: 12 Gauge Projectile Weight: 30 gram **Cartridge, Shotgun, 12G, Long Range, Irritant**

Ū,

Description

The Long Range IMP (Irritant Multi Purpose) round is designed for use in operations where CS deployment is required and where weather, climate or water immersion (up to 10m) is a factor. It can be fired at ranges up to 35 metres and will produce an immediate, large volume cloud of CS particles up to 10 metres behind a barricade.

(Waterproof)

The round incorporates a frangible projectile filled with micronized CS and stainless steel powder, which reduces the risk of ricochet and over penetration. 🔓 primetake

PT1038A

VERSION 6

SPECIFICATION

Payload: Micronised CS powder / Stainless Steel powder mix Case Material: Aluminium Operational Temperatures: -21°C to +63°C Safety Temperatures: -45°C to +71°C Mean Velocity: 350 - 400m/s at 2 metres Accuracy: 1m x 1m Target at 35 metres Penetration: 30-60 minute fire doors/commercial glass Mean Chamber Pressure: 400 - 600 bar Range: Up to 35 metres Propellant Type: Double Based Nitrocellulose Primer Type: Shotshell Primer Weapon Compatibility: 3" chamber magnum proofed shotgun (true cylinder - unchoked)

TRANSPORT & PACKAGING DETAILS

Packaging: M2A1	Packaging: Fibreboard Box
Dimensions mm: 306x156x192	Dimensions mm: 340x240x140
Qty per Outer Pack: 120	Quantity Per Outer Pack: 200
Gross Weight: 8.87kg	Gross Weight: 10.26kg
Maximum NEQ: 0.14kg	Maximum NEQ: 0.25kg
Proper Shipping Name: Ammunition, tear producing	
UN Serial Number: 0301	
Hazard Class: 1.4G (6.1 & 8)	
Shelf Life: 3 years under controlled conditions	
Storage requirements: To remain within original packaging,	
stored between +5°C to +30°C with a relative humidity not	
exceeding 70%.	

Find out more sales@primetake.com

We are constantly reviewing our products. All specifications are to be used as a guide and may vary so please check that the specification meets your requirements.