

PRODUCT DATA SHEET

PT1528A

VERSION 6



OVERVIEW

12 Gauge - Irritant

Code: PT1528A

Cal: 12 Gauge

Cartridge, Shotgun, 12G, Irritant, Short Range, HP (Waterproof)

Description

The Short Range IMP (Irritant Multi Purpose) round is designed for use in operations where CS deployment is required and where weather, climate or water immersion (up to 10m) is a factor. It can be fired at close range, with a recommended stand-off distance of 25mm from the target and produces an immediate, large volume cloud of CS particles up to 10 metres behind a barricade.

The round can be deployed against doors and windows with the ability to disrupt locks and hinges. It can also be deployed against soft skinned vehicles.

The round incorporates a loose filled payload mixture of micronized CS and refined Bismuth powder, which reduces the risk of ricochet and over penetration.

SPECIFICATION

- Payload: Micronised CS powder / Refined Bismuth powder mix
Case Material: Aluminium
Operational Temperatures: -21°C to +63°C
Safety Temperatures: -45°C to +71°C
Penetration: 30-60 minute fire door
Recommended Stand-Off: 25mm
Mean Chamber Pressure: 400 - 600 bar
Propellant Type: Double Based Nitrocellulose
Primer Type: Shotshell Primer
Weapon Compatibility: 3" chamber magnum proofed shotgun (true cylinder - unchoked)

TRANSPORT & PACKAGING DETAILS

- Packaging: M2A1 vs Fibreboard Box
Dimensions mm: 306x156x192 vs 340x240x140
Qty per Outer Pack: 120 vs 200
Gross Weight: 10.34kg vs 12.69kg
Maximum NEQ: 0.187kg vs 0.312kg
Proper Shipping Name: Ammunition, tear producing
UN Serial Number: 0301
Hazard Class: 1.4G (6.1 & 8)
Shelf Life: 3 years under controlled conditions
Storage requirements: To remain within original packaging, stored between +5°C to +30°C with a relative humidity not exceeding 70%.

Find out more

sales@primetake.com

We are constantly reviewing our products. All specifications are to be used as a guide and may vary so please check that the specification meets your requirements.