

## PRODUCT DATA SHEET

PT3581

VERSION 3



### OVERVIEW

## 12 Gauge - Practice & Training

Code: PT3581

Cal: 12 Gauge

**Cartridge, 12G, T-Less Blank**

### SPECIFICATION

Case Material: Green Plastic / Brass Ferrule

Operational Temperatures: -21°C to +63°C

Safety Temperatures: -45°C to +71°C

Recommended Stand-off Distance: 25mm

Primer Type: Shotshell Primer

Weapon Compatibility: 3" chamber magnum proofed shotgun  
(true cylinder - unchoked)

### Description

The 12G T-Less Blank round has been designed as a practice / training aid to simulate entry tactics and assist with function training of shotguns. The T-Less blank can be used as an alternative to Primetake's 12G Tea Blank, where there is no requirement for a loud report or smoke during the training exercise. The 12G T-Less blank produces the nominal sound of the primer ignition only.

### Performance/Safety

The 12G T-Less Blank does not contain a payload, therefore it produces no damage to the target or represent a ricochet risk however Primetake recommends a minimum safety distance of 2 metres.

This round has been designed for use in pump action shotguns only.

### TRANSPORT & PACKAGING DETAILS

Packaging: Fibreboard Box

Dimensions mm: 340x240x140

Quantity Per Outer Pack: 250

Gross Weight: 3.23kg

Maximum NEQ: 0.0005kg

Proper Shipping Name: Cartridges for weapons, blank

UN Serial Number: 0014

Hazard Class: 1.4S

Shelf Life: 5 years under controlled conditions

Storage requirements: To remain within original packaging, stored between +5°C to +30°C with a relative humidity not exceeding 70%.

Find out more

**sales@primetake.com**

We are constantly reviewing our products. All specifications are to be used as a guide and may vary so please check that the specification meets your requirements.