

# PRODUCT DATA SHEET



## 8. SPECIALIST SMALL ARMS AMMUNITION Cartridge, 300 AAC BLK - Training

**Primetake Part - PT4520D**  
Catalogue No. 08.02.4520D  
Version 1

### Product and Packing Details

WEIGHT	15.41g approx
NET EXPLOSIVE QUANTITY	1.633g per article nominal
SHELF LIFE	5 years under controlled storage conditions
PACKAGING	M2A1
DIMS mm	306x156x192
QTY PER OUTER PACK	600
MAXIMUM NEQ	0.980kg
PROPER SHIPPING NAME	Cartridges, small arms
UN SERIAL NUMBER	0012
HAZARD CLASS	1.4S



#### Methods of Use

The Primetake specialist 300 BLK range has been designed for assault rifles and high accuracy bolt-action rifles. The 300 BLK frangible projectile is designed to minimize the environmental hazards associated with the use of lead bullets. They are ideal for close quarter training due to elimination of splash back and ricochets that are typical of conventional bullets.

#### Description

The 110 grain frangible projectile has been designed to break up into small pieces upon impact with hardened steel or other materials that are harder than the projectile itself. The projectile is not jacketed or plated. The copper/tin material is non-hazardous and recyclable, which allows for less expensive range operation. The consistent uniformity of the projectile gives these bullets exceptional accuracy, reliable functioning and the same recoil characteristics as conventional projectiles.

This 300 BLK ammunition, as for all Primetake's ammunition, has precision manufactured components and are hand built to high specifications, thus achieving a high level of accuracy and consistency.

#### Performance/Safety

Recommended barrel twist rate 1:6 to 1:8. Accuracy fired from match quality barrel at 75 metres  $\leq 1.25$  M.O.A.

Primetake are able to assist with ballistic data for specific weapon/sight combinations. Results will vary according to rifle specification. Range Safety Template provided on request.

Articles should remain within the original sealed package and be stored within a temperature controlled environment of +5°C to +30°C; relative humidity should not exceed 70%. Storage outside of these conditions will not be warranted and may reduce the shelf life and lead to the articles not functioning as intended.

**At Primetake we constantly review our products—all specifications are a guide and may vary so please check that the latest specification meets your requirements**

Reepham Road, Fiskerton, Lincoln, LN3 4EZ, United Kingdom Phone: +44 (0)1522 752323 Fax: +44 (0)1522 752484  
Email: sales@primetake.com Web: www.primetake.com